


Project Name

Qty

Catalog / Part Number

LRMHS | Luci RIMiT hs

Color management
MacAdamL90>B10
50K1 years
warranty

Model No.(Open end)

LRMHS - T□□□□ - □ - □ - DF - I - 4

Model No.(Connector)

LRMHS - T□□□□ - □ - □ - DF - I - 4 (C)

Product Name	Length	Lead wire	Light source color	Tube type	Environment	Wattage	Connector
LRMHS	Custom order length	W : Both ends S : One end	N : 5000K W : 4000K WW : 3500K L30 : 3000K L27 : 2700K L24 : 2400K	DF : Diffuser	I : Indoor	4 : 4.5 W/m	(C) : Connector

Specification

Wattage (Code)	4
Wattage (W/m)	4.5
Weight	65g / 1008 mm
Luminaire efficacy (lm/W) @2700K	27.8

Luman output

Light source color (Code)

	Delivered CCT	Ra	Luminaire flux (lm/m)
N	5000K	4500K Ra 92	158
W	4000K	3600K Ra 91	139
WW	3500K	3200K Ra 93	144
L30	3000K	2800K Ra 92	136
L27	2700K	2500K Ra 92	125
L24	2400K	2200K Ra 91	110

General Specification

Input voltage	DC24V
Environment	Indoors (no condensation)
Max. length Per circuit	3.5m
Material (body)	Polycarbonate, Aluminum
Certification	CE
Dimmable	Yes (0-10V/1-10V, DMX, DALI, PWM, Casambi)


External dimensions

Both ends lead wire, Open end




Light Intensity

LRMHS-T1008□-L27-DF-I-4




Light source color 2700K
 Brightness 31 cd
 LuminoMR flux 125 lm
 Color rendering index Ra 92

Cross sectional view with accessories




Cross sectional view with accessories



Accessories




- 1 Mounting clip N for RIMiThs
Model No : LRMHS-PT-N
5 pcs /1 bag



Recommended screw: Flat head screw M2.3




- 2 Magnet set H
Model No : MG-H
5 pcs /1 bag



M1.4



- 3 Power supply cable 3M with TR connector
Model No : CAD-3000-MEFE-O
1 pcs per circuit for connecting the LED fixture
to power supply or dimmer driver.



Luci Pte. Ltd.
E-mail info@luci.co.jp

Singapore World HQ

Hong Kong Marketing Office

13A Bukit Pasoh Road, Singapore 089827

Unit 601-02, 6/F Union Park Tower, 168 Electric Road, Fortress Hill, Hong Kong


TEL +65-6291-2410

TEL +852-2219-8462




External dimension


Both ends lead wire, Open end



Both ends lead wire, Connector



One end lead wire, Open end



One end lead wire, Connector



Custom order length

Length(Code)	Fitting length(mm)	Wattage	Mounting Clip
0033	32.2	0.1	1 pcs
0058	57.2	0.2	
0083	82.2	0.3	
0108	107.2	0.5	2 pcs Recommended pitch 60 to 230mm
0133	132.2	0.6	
0158	157.2	0.7	
0183	182.2	0.8	
0208	207.2	0.9	
0233	232.2	1.0	
0258	257.2	1.1	3 pcs Recommended pitch 140 to 370mm
0283	282.2	1.2	
0308	307.2	1.4	
0333	332.2	1.5	
0358	357.2	1.6	
0383	382.2	1.7	
0408	407.2	1.8	
0433	432.2	1.9	
0458	457.2	2.0	
0483	482.2	2.1	
0508	507.2	2.3	
0533	532.2	2.4	
0558	557.2	2.5	
0583	582.2	2.6	
0608	607.2	2.7	
0633	632.2	2.8	4 pcs Recommended pitch 250 to 400mm
0658	657.2	2.9	
0683	682.2	3.1	
0708	707.2	3.2	
0733	732.2	3.3	
0758	757.2	3.4	
0783	782.2	3.5	
0808	807.2	3.6	
0833	832.2	3.7	
0858	857.2	3.8	
0883	882.2	4.0	
0908	907.2	4.1	
0933	932.2	4.2	
0958	957.2	4.3	
0983	982.2	4.4	5 pcs Recommended pitch 315 to 375mm
1008	1007.2	4.5	
1033	1032.2	4.6	
1058	1057.2	4.7	
1083	1082.2	4.9	
1108	1107.2	5.0	
1133	1132.2	5.1	
1158	1157.2	5.2	
1183	1182.2	5.3	
1208	1207.2	5.4	
1233	1232.2	5.5	
1258	1257.2	5.7	
1283	1282.2	5.8	
1308	1307.2	5.9	
1333	1332.2	6.0	
1358	1357.2	6.1	
1383	1382.2	6.2	
1408	1407.2	6.3	
1433	1432.2	6.4	
1458	1457.2	6.6	
1483	1482.2	6.7	
1508	1507.2	6.8	



Luci Pte. Ltd.
E-mail info@luci.co.jp

Singapore World HQ

Hong Kong Marketing Office

13A Bukit Pasoh Road, Singapore 089827


Unit 601-02, 6/F Union Park Tower, 168 Electric Road, Fortress Hill, Hong Kong

TEL +65-6291-2410

TEL +852-2219-8462



System configuration diagram



- ① Total product length per Dimmable driver depends on capacity of the Dimmable driver. Recommended loading factor is 70% (without dimming) or 60% (with dimming).
- ② Product length per circuit shall not exceed maximum product length per circuit. If the product length per circuit exceeds the maximum, split into multiple circuits.
- ③ To minimize voltage drop, select appropriate wire gauge/diameter and consider the cable length between Dimmable driver and the top of luminaire referring to the following table. If longer cable distances are required, use thicker wires or reduce the loading of the LED fixtures in the circuit.

Dimmable driver

Model No.	Size (mm) (L × W × H)
PX0408	140 × 50 × 26
DALI6010	168 × 39 × 30
DIM-S1L10V-0	175 × 56 × 28
PWM-200-24	195 × 68 × 39.5
PWM-120-24	191 × 63 × 37.5
PWM-90-24	171 × 63 × 37.5
PWM-60-24	150 × 53 × 35
PWM-40-24	150 × 53 × 35

Dimmable driver			PX0408 (8A × 4ch)-Use 1ch only	PX0408 (8A × 4ch)-Use 1ch only	PWM-200-24	PWM-120-24	PWM-90-24	PWM-60-24	PWM-40-24
			DALI6010 (10A × 1ch)	DALI6010 (10A × 1ch)					
			DIM-S1L10V-0 (10A × 1ch)	DIM-S1L10V-0 (10A × 1ch)					
			connectable up to 5A, when using 200W DC24V PSU as 60% load factor	connectable up to 3.75A, when using 150W DC24V PSU as 60% load factor	connect up to 140W as 70% load	connect up to 84W as 70% load	connect up to 63W as 70% load	connect up to 42W as 70% load	connect up to 28W as 70% load
Model No.	Wattage (W/m)	Max. length per circuit (m)	① Connectable length per Dimmable driver (m)						
			* Split into multiple circuit						
LRMHS-T**.*-DF-I-4	4.5	3.5	26.6*	20*	31.1*	18.6*	14*	9.3*	6.2*

